

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/088207 A1

(51) International Patent Classification⁷: G10K 11/178

(74) Agents: SLINGSBY, Philip, Roy et al.; Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(21) International Application Number: PCT/GB03/01565

(22) International Filing Date: 14 April 2003 (14.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0208421.8 12 April 2002 (12.04.2002) GB

(71) Applicant and

(72) Inventor: WRIGHT, Selwyn, Edgar [GB/GB]; 22 Moor Lane, Highburton, Huddersfield, West Yorkshire HD8 0QS (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VUKSANOVIC, Branislav [YU/GB]; 54 Gleadsmoss Lane, Oakwood, Derby DE21 2BP (GB). ATMOKO, Hidajat [ID/GB]; 25 Bow Street, Huddersfield, West Yorkshire HD1 4BJ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: ACTIVE NOISE CONTROL SYSTEM IN UNRESTRICTED SPACE



(57) Abstract: The adaptive speed to changes in a primary source noise (1) is increased through a noise detecting means (4) feeding parallel multi-passband means (5) and multi-transverse adaptive filter means (6), where each adaptive filter has its own individual adaptive step size means (11) adjusted automatically according to the signal strength at each passband output. The output from each of the multi-adaptive filter means (6) drives a secondary canceling source generating means (7) where each multi-adaptive filter means (5) is automatically adjusted to produce minimum sound in its passband at an error detecting means (3). Alternatively, the output from the noise detecting means (4) is negated through a negation means (13), passed through a plant neutralization inverse means (14) and an inverse delay means (15) before driving the secondary source generating means (7). The secondary source output is aligned and match in amplitude to that of the primary source (1), through a delay buffer means (16) and an amplitude regulator means (17), which are adjusted successively until the output at the error detector means (3) is a minimum.